

GM DIGITAL MIXER M16



M16

SPECIFICATION

- 12 MIC input (independent 48V phantom power switch), 2 groups of lotus jack stereo input, 1 set of digital input, AES input and output
- MIC input channel (Linked) odd-even, each channel TFT LCD guide display.
- Channel name and background color can be customized edit.
- Shutdown parameters are automatically saved, without worrying about data loss
- 6 DCA masters and 6 mute masters Built-in signal generator (pink noise/positive wave/whitenoise)
- Each input is 5-segment parameter EQ adjustable, arbitrary high-low pass filter frequency division
- With sound card /MP3, support U disk playback, recording
- With real-time spectrum RTA function (color editable) 10-channel mixer signal output (main output L/R, 8-channel AUX output)
- Integrated RTA real-time spectrum display function
- 16 channels mixing signal output (main output L/R, 14 AUX output)
- Each output is 15 sections of parameter EQ adjustable (main output is 31 sections), high and low pass Filter arbitrary frequency division
- Built-in 4-channel independent effector, using French DREAM professional effect DSP chip
- Integrated automatic mixing function
- Chinese and English interface display, PC/iPad/ Android wireless remote control
- 33 100mm, ALPS high-precision electric push
- Linux operating system, non-Android system, no crash and no virus interference
- 10.1 inch 1280*800 HD capacitive touch screen display
- RS232 central control on line control



Location

14, Woods Road,
Chennai - 600002
Tamil Nadu, India.

Email

gmgiri14@gmail.com
info@gmaudio.co.in
gmgiri@gmaudio.co.in

Phone

044 - 28613223

Mobile

98840 31505