

XD6PF

POWERED GM AUDIO

PASSIVE / BI-AMP
DOUBLE 6' LINE ARRAY

18
EIGHTEEN
SOUND



LF DRIVER



6ND430

2 x 260W 4Ω 8Ω 16Ω

HF DRIVER



HD1050

1 x 100W 8Ω

HEAVY DUTY

620W

PROGRAM POWER

FEATURES:

6ND460 Neodymium - LF -----

- 92,5 dB SPL 1W / 1m average sensitivity
- Frequency Range 63 Hz - 5500 Hz
- Crossover Point 63 Hz - 1.4 KHz
- 45 mm (1,77 in) aluminum voice coil
- 200 W AES power handling
- Neodymium motor assembly
- Weather protected cone
- Improved heat dissipation via unique basket design
- Surround Shape - Single roll - Rubber

HD1050 Ferrite - HF -----

- 107 dB SPL 1W / 1m average sensitivity
- Frequency Range 1.6 KHz - 20 KHz
- Crossover Point 1.4 KHz - 20 KHz
- 1 inch exit throat
- 44 mm (1 3/4 inch) voice coil diameter
- 100 Watt program power handling
- Titanium dome over PEN suspension
- Proprietary phase plug design



ORIGINAL
18SOUND ITALY SPEAKERS



+91 98410 31505
+91 98840 31505



gmgiri14@gmail.com
gmgiri@gm.audio.co.in



14, Woods Road, Chennai - 600002
Tamil Nadu, India.